


AC Laminated Solenoids

TT02

**Push/Pull:**

- Pull or push types

Connection:

- Lugs or flying leads

H x W x L:

- 37mm x 57mm x 37mm

Stroke:

- Up to 16mm

Voltage:

- 6 - 415VAC

Force:

- Coils can be designed for various duty cycles to achieve the optimum force

TT04

**Push/Pull:**

- Pull or push types

Connection:

- Lugs or flying leads

H x W x L:

- 54mm x 70mm 56mm

Stroke:

- Up to 24mm

Voltage:

- 6 - 415VAC

Force:

- Coils can be designed for various duty cycles to achieve the optimum force

TT06

**Push/Pull:**

- Pull or push types

Connection:

- Lugs or flying leads

H x W x L:

- 54mm x 70mm 56mm

Stroke:

- Up to 24mm

Voltage:

- 6 - 415VAC

Force:

- Coils can be designed for various duty cycles to achieve the optimum force

TT10

**Push/Pull:**

- Pull or push types

Connection:

- Lugs or flying leads

H x W x L:

- 73mm x 95mm x 60mm

Stroke:

- Up to 30mm

Voltage:

- 6 - 415VAC

Force:

- Coils can be designed for various duty cycles to achieve the optimum force

A141

**Push/Pull:**

- Pull or push types

Connection:

- Lugs or flying leads

H x W x L:

- 56mm x 78mm x 47mm

Stroke:

- Up to 24mm

Voltage:

- 6 - 415VAC

Force:

- Coils can be designed for various duty cycles to achieve the optimum force

A142

**Push/Pull:**

- Pull or push types

Connection:

- Lugs or flying leads

H x W x L:

- 56mm x 78mm x 49mm

Stroke:

- Up to 24mm

Voltage:

- 6 - 415VAC

Force:

- Coils can be designed for various duty cycles to achieve the optimum force

A143

**Push/Pull:**

- Pull or push types

Connection:

- Lugs or flying leads

H x W x L:

- 56mm x 78mm x 50mm

Stroke:

- Up to 28mm

Voltage:

- 6 - 415VAC

Force:

- Coils can be designed for various duty cycles to achieve the optimum force

A500

**Push/Pull:**

- Pull or push types

Connection:

- Lugs or flying leads

H x W x L:

- 60mm x 78mm x 59mm

Stroke:

- Up to 28mm

Voltage:

- 6 - 415VAC

Force:

- Coils can be designed for various duty cycles to achieve the optimum force

A600

**Push/Pull:**

- Pull or push types

Connection:

- Lugs or flying leads

H x W x L:

- 94mm x 116mm x 80mm

Stroke:

- Up to 40mm

Voltage:

- 6 - 415VAC

Force:

- Coils can be designed for various duty cycles to achieve the optimum force

A700

**Push/Pull:**

- Pull or push types

Connection:

- Lugs or flying leads

H x W x L:

- 133mm x 154mm x 118mm

Stroke:

- Up to 50mm

Voltage:

- 6 - 415VAC

Force:

- Coils can be designed for various duty cycles to achieve the optimum force